

XF Series

Solid Door Reach-In Freezers

MODEL #XF-3-HC

CABINET CONSTRUCTION

Heavy duty all-stainless steel construction includes corrosion-resistant 304 stainless steel interior and durable 430 stainless steel exterior.

Foamed-in-place CFC- and HCFC-free polyurethane insulation enhances the structural integrity of the cabinet and helps increase energy efficiency.

Removable one-piece grill simplifies cleaning and servicing.

Stainless steel solid doors have stay-open feature beyond 90° for easy loading, but will self-close under 90° to save energy. Each door is outfitted with an easy-to-grasp full length handle

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Bottom-mounted condensing unit positioned for easy maintenance.

“No stoop” lower shelf raises product to a higher level for easy access.

SHELVING

9 gray epoxy-coated steel shelves included. Each accommodates up to 120 lb.

MODEL FEATURES

Preprogrammed digital controls feature auto-defrost function.

Shelf rails accommodate full size food pans for storage flexibility. Optional bun pan rails accommodate full size bun pans.

Interior back panel separates shelf and back wall to promote proper airflow.



★ Conforms to UL & NSF-7 Standards

Xiltek

XF Series REACH-IN FREEZER

Keep ingredients within a safe temperature range in a sleek, durable, and easy-to-clean environment

SPECIAL FEATURES

- Self-closing doors with convenient stay-open feature
- Easy-to-clean 430 series stainless steel exterior
- Corrosion-resistant 304 series stainless steel interior
- Temperature range of (-8)°F - (-1)°F
- 9 shelves included; versatile shelf slide design also accepts full size food pans
- Environmentally-safe R290 refrigerant
- Digital temperature controller with automatic defrost function
- 115V; 1 ¼ HP
- ETL Safety & Sanitation Listed



Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
XF-3-HC	3	9	80 9/10 2054	32 1/4 818	82 1/4 2095	72 2040	1 1/4	115/60/1	12	5-20P 

XF Series

Solid Door Reach-In Freezers

MODEL #XF-3-HC

Xiltek

Dimensions

Exterior Dimensions	80 ⁷ / ₈ "W x 32 ¹ / ₄ "D x 82 ¹ / ₂ "H
Interior Dimensions	76 ¹ / ₄ "W x 27 ¹ / ₈ "D x 60 ¹ / ₄ "H
Net Volume	72 cu. ft.
Net Weight	615 lb.
Gross Weight	693 lb.
Packaging Dimensions	83 ¹ / ₂ "W x 34 ³ / ₄ "D x 85 ¹ / ₂ "H

Construction

Exterior Material	430 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-In-Place Polyurethane
Shelf Size	(6) 20 ⁷ / ₈ "W x 25 ³ / ₁₆ "D & (3) 22 ¹ / ₈ "W x 25 ³ / ₁₆ "D
Shelf Material	Epoxy-Coated Steel
Shelf Load Capacity	120 lb.



Cooling

Temperature Range	(-8)°F - (-1)°F
Refrigerant	R290
Max. Ambient Temperature	100°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1 ¹ / ₄

Electrical

Voltage	115
Amps	12
Hz	60
Phase	1
Plug Type	NEMA 5-20P
Electrical Cord Length	96"

PLAN VIEW



NEMA 5-20P