

XRM Series

Glass Door Merchandiser



MODELS | #XRM-49S-HC

XRM SERIES - GLASS DOOR REFRIGERATOR

Used for the merchandising and storage of hermetically sealed products for sale

CABINET CONSTRUCTION

Heavy duty construction includes white-coated aluminum interior walls and stainless steel floor. Exterior features peel and chip-resistant, powder-coated cold rolled steel that is durable and permanent.

LED lighted interior saves energy by producing less heat and maximizes product visibility in display area.

Foamed-in-place CFC- and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

One-piece grill is easily removed for cleaning and servicing.

2 doors feature inside and outside tempered glass panes. Self-closing, sliding doors won't fog with use, ensuring clear product visibility at all times. Unlike swing doors, they don't require clearance outside the unit to open.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Bottom-mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to a higher level.

SHELVING

8 white epoxy-coated steel shelves included. Each accommodate up to 90 lb.

MODEL FEATURES

Copper evaporator coil eliminates the potential of corrosion.

Convenient clean-out drain built into cabinet floor.

Easy to read digital controls.

SPECIAL FEATURES

- Two sliding glass doors
- Interior LED lighting
- (8) epoxy-coated steel shelves included
- Foamed-in-place polyurethane insulation
- Bottom mount condensing unit
- Removable door gasket for easy cleaning
- Automatic defrosting
- Stainless steel floor
- Copper evaporator
- Available in black or white powder-coated steel exterior
- Eco-friendly R290 hydrocarbon refrigerant



Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
XRM-49S-HC	2	8	53.1 1350	31.9 810	84.38 2144	49 1390	1/4+	115/60/1	4.3	5-15P 

XRM Series

Glass Door Merchandiser

MODELS | #XRM-49S-HC

Xiltek

TECHNICAL DATA

Dimensions

Exterior Dimensions	53⅞"W x 31⅞"D x 84⅜"H
Interior Dimensions	50"W x 28⅜"D x 61⅞"H
Net Volume	49 cu. ft.
Net Weight	437 lbs.
Gross Weight	480 lbs.
Packaging Dimensions	54¼"W x 33"D x 84½"H

Construction

Exterior Material	Coated steel
Interior Material	Painted aluminum
Door Type	Glass sliding
Insulation Material	Foamed-in -place polyurethane
Shelf Size	(8) 24⅜" x 23⅝"
Shelf Material	Epoxy-coated steel
Shelf Load Capacity	90 lb.

Cooling

Temperature Range	33°F-40°F
Refrigerant	R290
Max. Ambient Temperature	90
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4

Electrical

Voltage	115
Amps	4.3
Hz	60
Phase	1
Plug Type	NEMA 5-15P
Electrical Cord Length	96"

PLAN VIEW

